

LYTRON HEAT EXCHANGER FAN SPECIFICATIONS

Fan (Part #)	Size	Rated Voltage (V)	Frequency (Hz)	Input Power (Watts)	Rate Cur. (Amps)	Locked Cur. (Amps)	Speed (RPM)	Max Air Flow M ³ /Min (CFM)	Max Pressure (H ₂ O) mm (in)	Noise (dbA)
Kona 102076-11	4.69" (120 mm) square	115	50	14	0.20	0.27	2700	2.6 (92)	8.0 (0.32)	42
			60	12	0.16	0.23	3100	3.0 (106)	8.0 (0.32)	46
Kona 102076-12	4.69" (120 mm) square	230	50	17	0.10	0.14	2700	2.6 (92)	8.0 (0.32)	42
			60	15	0.08	0.12	3100	3.0 (106)	8.0 (0.32)	46
Marin 101116-11	6.77" (172 mm) round	115	50	31	0.26	0.41	2850	5.8 (205)	16 (0.63)	50
			60	31	0.25	0.43	3400	6.4 (226)	20 (0.79)	55
Marin 101116-12	6.77" (172 mm) round	230	50	29	0.12	0.19	2850	5.8 (205)	16 (0.63)	50
			60	29	0.12	0.19	3400	6.4 (226)	20 (0.79)	55
Ostro 100236-11	10.0" (254 mm) round	115	50	31	0.30	0.53	1400	13.0 (460)	8.0 (0.32)	52
			60	33	0.29	0.51	1650	15.5 (550)	10 (0.40)	55
Ostro 100236-12	10.0" (254 mm) round	230	50	31	0.14	0.26	1400	13.0 (460)	8.0 (0.32)	52
			60	33	0.14	0.25	1650	15.5 (550)	10.0 (0.40)	55

